

# ARTESYN LPS200-M SERIES

250 Watts



Advanced Energy's Artesyn LPS200-M series medically-approved AC-DC power supplies are available with a nominal main output of 5 V, 12 V, 15 V, 24 V or 48V. Auxiliary 12 V fan output is also provided. LPS200-M power supplies provide 125 Watts of output power with free air convection cooling or up to 250 Watts with 30 CFM of forced air. All models have a power factor of 0.99 typical and a 3 x 5 x 1.32 inch form factor.

## AT A GLANCE

### Total Power

125 to 250 Watts

### Input Voltage

90 to 264 VAC

### # of Outputs

Single

## SPECIAL FEATURES

- Medical and ITE safeties
- Active power factor correction
- 3" x 5" footprint
- Less than 1U high
- EN61000-3-2 compliant
- Remote sense
- Power fail
- Adjustable main output
- Built-in Class B EMI filter
- Overvoltage protection
- Overload protection
- Thermal overload protection
- Isolated 12 V Fan output
- LPX200 enclosure kit available
- RoHS compliant

## SAFETY

- TUV 62368, 60601-1
- UL 62368, 60601-1
- cULus 62368, 60601-1
- CB Certificate & report
- CE Mark (LVD)
- UKCA Mark

## ELECTRICAL SPECIFICATIONS

Input	
Input range	90 to 264 VAC; 120 to 300 VDC
Frequency	47 to 63 Hz
Inrush current	50 A max., cold start @ 25°C
Efficiency	86% typical at full load
EMI/RFI	FCC Class B conducted; CISPR22 Class B conducted; EN55022 Class B conducted; VDE0878PT3 Class B conducted
Power factor	0.99 typical
Safety ground Leakage current	275 $\mu$ A @ 50/60 Hz, 264 Vac input
Output	
Maximum power	125 W for convection (100 W for LPS202-M); 250 W (200 W for LPS202-M) with 30CFM forced air
Adjustment range	$\pm$ 10% minimum on the main outputs
Fan output	12 V @ 0.5 A convection, @ 1 A forced air isolated, $\pm$ 10%
Hold-up time	16 ms @ 250 W load, 120 Vac input
Overload protection	Short circuit protection on all outputs. Case overload protected @ 110% to 160% above rating
Overvoltage protection	15% to 50% above nominal output
Logical Control	
Power failure	Open collector logic signal goes high 100 to 500 msec after main output; it goes low at least 6 msec before loss of regulation
Remote sense	Compensates for 0.5 V lead drop min. Will operate without remote sense connected. Reverse connection protected.

## ENVIRONMENTAL SPECIFICATIONS

Operating temperature	0°C to 50°C ambient derate each output as 2.5% per degree from 50° to 70°C. -20°C start up
Storage temperature	-40°C to +85°C
Electromagnetic susceptibility	Designed to meet EN61000-4; -2, -3, -4, -5, -6, -8, -11 Level 3
Humidity	Operating; non-condensing 10% to 95% RH
Vibration	IEC68-2-6 to the levels of IEC721-3-2
MTBF calculated	1 million hours at full load and 25°C ambient conditions. 230 Vac input, Bellcore

## ORDERING INFORMATION

Model Number	Output Voltage	Minimum Load	Maximum Load with Convection Cooling	Maximum Load with 30CFM Forced Air	Peak Load <sup>1</sup>	Regulation <sup>2</sup>	Ripple P/P(PARD) <sup>3</sup>
LPS202-M	5 V	0 A	20 A	40 A	44 A	± 2%	50 mV
LPS203-M	12 V	0 A	10.3 A	20.8 A	22 A	± 2%	120 mV
LPS204-M	15 V	0 A	8.3 A	16.6 A	18 A	± 2%	150 mV
LPS205-M	24 V	0 A	5.2 A	10.4 A	11.5 A	± 2%	240 mV
LPS208-M	48 V	0 A	2.6 A	5.2 A	5.8 A	± 2%	480 mV

<sup>1</sup> Peak current lasting <30 seconds with a maximum 10% duty cycle.

<sup>2</sup> At 25°C including initial tolerance, line voltage, load currents and output voltages adjusted to factory settings.

<sup>3</sup> Peak-to-peak with 20 mHz bandwidth and 10 µF (tantalum capacitor) in parallel with a 0.1 µF capacitor at rated line voltage and load ranges.

<sup>4</sup> This product is a Component Power Supply and is only for inclusion by professional installers within other equipment and must not be operated as a standalone product. EMC compliance to appropriate standards must be verified at the system level. This product is for sale to OEMs and System Integrators, including through Distribution Channels. It is not intended for sale to End Users.

## PIN ASSIGNMENTS


Connector	LPS200-M	
SK1	Pin 1	Neutral
	Pin 3	LINE
SK2	TB-1	COMMON
	TB-2	MAIN OUTPUT
SK3	Pin 1	+V1 REMOTE SENSE
	Pin 2	-V1 REMOTE SENSE
	Pin 3	N/C
	Pin 4	N/C
	Pin 5	+POWER FAIL
	Pin 6	COMMON
	Pin 7	N/C
	Pin 8	COMMON
	Pin 9	+12 V FAN
	Pin 10	+12 FAN RETURN (ISOLATED)

**MATING CONNECTORS**

AC Input (SK1)	Molex 09-50-8031 (connector) PINS: 08-52-0072
AC Ground	Molex 01-90020001
DC Output (SK2)	Molex 19141-0058 or 19099-0044 Spade lug based on Cable Ampacity/AWG
Control Sense (SK3)	Molex 90142-1110 (USA) PINS: 90119-2110 or Amp: 87977-3 PINS: 87309-8 or Landwin: 2580S1003 PINS: 2583T021V
Artesyn Embedded Power Connector Kit #70-841-020, includes all of the above.	

- 1 Specifications subject to change without notice.
- 2 All dimensions in inches (mm), tolerance is ± 0.02" (± 0.5 mm)
- 3 Mounting holes MH1 and MH2 should be grounded for EMI purposes.
- 4 Mounting hole MH1 is safety ground connection.
- 5 Specifications are for convection rating at factory settings at 115 VAC input, 25°C unless otherwise stated.
- 6 This power supply requires mounting on metal standoffs 0.20" (5m) in height.
- 7 Warranty: 2 years
- 8 Weight: 0.75 lb/0.34 kg

MECHANICAL DRAWING





For international contact information,  
visit [advancedenergy.com](http://advancedenergy.com).

[powersales@aei.com](mailto:powersales@aei.com) (Sales Support)  
[productsupport.ep@aei.com](mailto:productsupport.ep@aei.com) (Technical Support)  
+1 888 412 7832

## ABOUT ADVANCED ENERGY

Advanced Energy (AE) has devoted more than three decades to perfecting power for its global customers. AE designs and manufactures highly engineered, precision power conversion, measurement and control solutions for mission-critical applications and processes.

Our products enable customer innovation in complex applications for a wide range of industries including semiconductor equipment, industrial, manufacturing, telecommunications, data center computing, and medical. With deep applications know-how and responsive service and support across the globe, we build collaborative partnerships to meet rapid technological developments, propel growth for our customers, and innovate the future of power.

PRECISION | POWER | PERFORMANCE

---

Specifications are subject to change without notice. Not responsible for errors or omissions. ©2022 Advanced Energy Industries, Inc. All rights reserved. Advanced Energy®, AE® and Artesyn™ are U.S. trademarks of Advanced Energy Industries, Inc.